

FEATURES

- ▶ Industrial Standard DIP-24 Package
- ▶ Fully Regulated Output Voltage
- ▶ I/O Isolation 3000VAC with Reinforced Insulation, rated for 300Vrms Working Voltage
- ▶ Low I/O Leakage Current < 2μA
- ▶ Operating Ambient Temp. Range -40°C to +77.5°C
- ▶ No Min. Load Requirement
- ▶ Short Circuit Protection
- ▶ Conducted EMI EN 55011/22 Class A Approved
- ▶ Medical EMC Standard with 4th Edition of EMI EN 55011 and EMS EN 60601-1-2 Approved
- ▶ Medical Safety with 1xMOPP & 2xMOOP per 3rd Edition of IEC/EN 60601-1 & ANSI/AAMI ES60601-1 Approved
- ▶ Risk Management Report Acquisition according to ISO 14971


PRODUCT OVERVIEW

Introducing the MINMAX MIDR03M series – a high isolation DC-DC converter modules featuring a reinforced insulation system. The I/O isolation voltage is specified at 3000VAC, rated for a 300Vrms working voltage.

Encased in a compact DIP-24 package, MIDR03M series is available in 15 models catering to 5V, 12V, and 24V input voltages, with options for single or dual output voltage configurations. The MIDR03M DC-DC converters present a cost-effective solution for applications in industrial controls, medical instrumentation, and consumer electronics that require a certified supplementary or reinforced insulation system to comply with the latest industrial or medical safety standards.

The MIDR03M series is approved to IEC/EN/ES 60601-1 3rd edition for 1xMOPP & 2xMOOP and comes with an ISO 14971 Medical Device risk management file, ensuring not only adherence to high-performance standards but also compliance with strict safety benchmarks.

Model Selection Guide

Model Number	Input Voltage	Output Voltage	Output Current	Input Current		Max. capacitive Load	Efficiency (typ.)
				Max.	@No Load		
	VDC	VDC	mA	@Max. Load mA(typ.)	@No Load mA(typ.)	μF	@Max. Load %
MIDR03-05S05M	5 (4.5 ~ 5.5)	5	600	1000	130	470	60
MIDR03-05S12M		12	250	960			62
MIDR03-05S15M		15	200	960			62
MIDR03-05D12M		±12	±125	1000			60
MIDR03-05D15M		±15	±100	1000			60
MIDR03-12S05M	12 (10.8 ~ 13.2)	5	600	420	60	470	60
MIDR03-12S12M		12	250	400			62
MIDR03-12S15M		15	200	400			62
MIDR03-12D12M		±12	±125	420			60
MIDR03-12D15M		±15	±100	420			60
MIDR03-24S05M	24 (21.6 ~ 26.4)	5	600	210	40	470	60
MIDR03-24S12M		12	250	195			64
MIDR03-24S15M		15	200	195			64
MIDR03-24D12M		±12	±125	210			60
MIDR03-24D15M		±15	±100	210			60

For each output


Input Specifications					
Parameter	Model	Min.	Max.	Unit	
Input Voltage Range	5V Input Models	4.5	5.5	VDC	
	12V Input Models	10.8	13.2		
	24V Input Models	21.6	26.4		
Input Surge Voltage (1 sec. max.)	5V Input Models	-0.7	7.5		
	12V Input Models	-0.7	15		
	24V Input Models	-0.7	30		
Short Circuit Input Power	All Models	---	2500	mW	
Input Filter		Internal Pi Type			
Conducted EMI		Compliance to EN 55011/22, class A			

Output Specifications					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Output Voltage Setting Accuracy		---	---	±4.0	%Vnom.
Output Voltage Balance	Dual Output, Balanced Loads	---	±2.0	±4.0	%
Line Regulation	Vin=Min. to Max. @Full Load	---	±0.3	±0.5	%
Load Regulation	Io=10% to 100%	---	±0.5	±1.0	%
Minimum Load	No minimum Load Requirement				
Ripple & Noise	0-20 MHz Bandwidth	---	---	50	mV _{P-P}
Temperature Coefficient		---	±0.01	±0.02	%/°C
Short Circuit Protection	Continuous, Automatic Recovery				


Isolation, Safety Standards					
Parameter	Conditions	Min.	Typ.	Max.	Unit
I/O Isolation Voltage	60 Seconds	3000	---	---	VAC
	Reinforced insulation, rated for 300Vrms working voltage				
Leakage Current	240VAC, 60Hz	---	---	2	μA
I/O Isolation Resistance	500 VDC	10	---	---	GΩ
I/O Isolation Capacitance	100kHz, 1V	---	20	---	pF
Safety Standards	ANSI/AAMI ES60601-1, CAN/CSA-C22.2 No. 60601-1				
Safety Approvals	ANSI/AAMI ES60601-1 1xMOPP & 2xMOOP recognition(UL certificate), IEC/EN 60601-1 3 rd Edition (CB-report)				
	UL/cUL 62368-1 recognition(UL certificate), IEC/EN 62368-1(CB-report)				

General Specifications					
Parameter	Conditions	Min.	Typ.	Max.	Unit
Switching Frequency		25	60	---	kHz
MTBF(calculated)	MIL-HDBK-217F@25°C, Ground Benign	1,000,000	---	---	Hours

Environmental Specifications			
Parameter	Min.	Max.	Unit
Operating Ambient Temperature Range (See Power Derating Curve)	-40	+77.5	°C
Case Temperature	---	+95	°C
Storage Temperature Range	-50	+125	°C
Humidity (non condensing)	---	95	% rel. H
Lead Temperature (1.5mm from case for 10Sec.)	---	260	°C

Power Derating Curve

Notes

- Specifications typical at Ta=+25°C, resistive load, nominal input voltage and rated output current unless otherwise noted.
- We recommend to protect the converter by a slow blow fuse in the input supply line.
- Other input and output voltage may be available, please contact MINMAX.
- Specifications are subject to change without notice.
- The repeated high voltage isolation testing of the converter can degrade isolation capability, to a lesser or greater degree depending on materials, construction, environment and reflow solder process. Any material is susceptible to eventual chemical degradation when subject to very high applied voltages thus implying that the number of tests should be strictly limited. We therefore strongly advise against repeated high voltage isolation testing, but if it is absolutely required, that the voltage be reduced by 20% from specified test voltage. Furthermore, the high voltage isolation capability after reflow solder process should be evaluated as it is applied on system.

Package Specifications
Mechanical Dimensions

Pin Connections

Pin	Single Output	Dual Output	Diameter mm (inches)
1	+Vin	+Vin	∅ 0.5 [0.02]
2	+Vin	+Vin	∅ 0.5 [0.02]
10	No Pin	Common	∅ 0.5 [0.02]
11	No Pin	Common	∅ 0.5 [0.02]
12	-Vout	No Pin	∅ 0.5 [0.02]
13	+Vout	-Vout	∅ 0.5 [0.02]
15	No Pin	+Vout	∅ 0.5 [0.02]
23	-Vin	-Vin	∅ 0.5 [0.02]
24	-Vin	-Vin	∅ 0.5 [0.02]


- ▶ All dimensions in mm (inches)
- ▶ Tolerance: X.X±0.25 (X.XX±0.01)
X.XX±0.13 (X.XXX±0.005)
- ▶ Pin diameter tolerance: X.X±0.05 (X.XX±0.002)

Physical Characteristics


Case Size	: 31.8x20.3x10.5 mm (1.25x0.80x0.41 inches)
Case Material	: Plastic resin (flammability to UL 94V-0 rated)
Pin Material	: Copper Alloy
Weight	: 12.4g

Test Setup
Input Reflected-Ripple Current Test Setup

Input reflected-ripple current is measured with an inductor L_{in} ($4.7\mu\text{H}$) and C_{in} ($220\mu\text{F}$, $\text{ESR} < 1.0\Omega$ at 100 kHz) to simulate source impedance. Capacitor C_{in} offsets possible battery impedance. Current ripple is measured at the input terminals of the module, measurement bandwidth is $0\text{--}500\text{ kHz}$.


Peak-to-Peak Output Noise Measurement Test


Use a C_{out} $0.33\mu\text{F}$ ceramic capacitor. Scope measurement should be made by using a BNC socket, measurement bandwidth is $0\text{--}20\text{ MHz}$. Position the load between 50 mm and 75 mm from the DC-DC Converter.


Technical Notes
Maximum Capacitive Load


The MIDR03M series has a limitation of maximum connected capacitance at the output. The power module may be operated in current limiting mode during start-up, affecting the ramp-up and the startup time. For optimum performance we recommend $220\mu\text{F}$ maximum capacitive load for dual outputs and $470\mu\text{F}$ capacitive load for single outputs. The maximum capacitance can be found in the data sheet.

Input Source Impedance

The power module should be connected to a low ac-impedance input source. Highly inductive source impedances can affect the stability of the power module. In applications where power is supplied over long lines and output loading is high, it may be necessary to use a capacitor at the input to ensure startup. A capacitor mounted close to the power module helps ensure stability of the unit, it is recommended to use a good quality low Equivalent Series Resistance ($\text{ESR} < 1.0\Omega$ at 100 kHz) capacitor of a $4.7\mu\text{F}$ for the 5V input devices and a $2.2\mu\text{F}$ for the 12V and 24V devices.


Output Ripple Reduction

A good quality low ESR capacitor placed as close as practicable across the load will give the best ripple and noise performance. To reduce output ripple, it is recommended to use $1.5\mu\text{F}$ capacitors at the output.


Thermal Considerations

Many conditions affect the thermal performance of the power module, such as orientation, airflow over the module and board spacing. To avoid exceeding the maximum temperature rating of the components inside the power module, the case temperature must be kept below 95°C . The derating curves are determined from measurements obtained in a test setup.

